

2 3 4 5 6 7 8

## SCALE: 1/4" = 1'-0"

NOTES:

1

- 1. COORDINATE ALL RECEPTACLE LOCATIONS WITH THE CABINETRY, CASEWORK AND FURNITURE, AS WELL AS WITH THE VOICE AND TECHNOLOGY OUTLET LOCATIONS PRIOR TO ROUGH-IN.
- 2. ALL RECEPTACLES MOUNTED ON FLOOR STANCHIONS MUST NOT EXCEED 5" TO THE TOP OF RECEPTACLES.
- 3. SEE ALL FSE-X SHEETS FOR ADDITIONAL ELECTRICAL REQUIREMENTS / INFORMATION.
- 4. ALL RECEPTACLES IN KITCHEN AREA SHALL HAVE GFCI PROTECTION WHERE THE GFCI PROTECTION IS ACCESSIBLE. GFCI PROTECTION SHALL BE BY GFCI TYPE RECEPTACLES OR GFCI CIRCUIT BREAKERS.
- 5. INSTALL ALL LIGHTING IN THE FREEZER AND COOLER AS REQUIRED.

## ENLARGED KITCHEN AREA - POWER PLAN

9	10			11	12 13	
						2203-2 
						44 145 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
KITCHEN EQUIPMENT SCHEDULE						
ARK DESCRIPTION	A VO	OLTAGE/Ø	CONNECTION TYPE	MOUNTING	KEMAKKS	$  {}^{K}   \mathbf{Z}   {}^{A}   {}^{A}  $
4     LIGHTS AND DOOR HEATER       5     COOLER COIL	10.0	120/1	B	N/A N/A	INSTALL ADDITIONAL LIGHTING IN THE COOLER/FREEZER. PROVIDE ALL WIRING AND MAKE ALL CONNECTIONS AS REQUIRED. PROVIDE A 30 AMP, 2 POLE, NEMA 4X FUSIBLE SAFETY SWITCH. FUSE AS REQUIRED. LOCATE AS DIRECTED.	
5A COOLER COMPRESSOR	5.9	208/3	В	N/A	PROVIDE A 30 AMP, 3 POLE, NEMA 3R FUSIBLE SAFETY SWITCH. FUSE AS REQUIRED. LOCATE AS DIRECTED. PROVIDE A 30 AMP, 2 POLE, NEMA 4X FUSIBLE SAFETY	
6 FREEZER COIL 6A FREEZER COMPRESSOR	9.8	208/1	B	N/A N/A	SWITCH. FUSE AS REQUIRED. LOCATE AS DIRECTED.         PROVIDE A 30 AMP, 3 POLE, NEMA 3R FUSIBLE SAFETY         SWITCH. FUSE AS REQUIRED. LOCATE AS DIRECTED.	AL AL
B FREEZER COIL HEAT TAPE	5.0	120/1	В	N/A	WIRE SERVICE TO FREEZER EVAPORATOR COIL THROUGH TIME CLOCK LOCATED AT CONDENSING UNIT.	
MIXER - 30 QUART	9.5	120/1	B	+48"		ARC HI DERRY
33     DISHWASHER W/ BOOSTER HEATER       3A     EXHAUST FAN	68.0	480/3	B	+66"	PROVIDE A 100 AMP, 3 POLE, NEMA 4X FUSIBLE SAFETY SWITCH. FUSE AS REQUIRED. LOCATE AS DIRECTED. MAKE ALL CONNECTIONS TO DISHWASHER CONTROL PANEL	
3A   EXHAUST FAN     35   DISPOSAL	10.0	208/3	В	N/A +12"	PROVIDE A 30 AMP, 3 POLE, NEMA 4X FUSIBLE SAFETY SWITCH. FUSE AS REQUIRED. LOCATE AS DIRECTED.	3850 H
3     TILT SKILLET       4     CONVECTION OVEN - DOUBLE DECK	5.0 9.8	120/1 120/1	A A	+30" +12"		S A C
CONVECTION OVEN - DOUBLE DECK	9.8 7.5 7.5	120/1 120/1 120/1	A A A	+30" +30" +60"		Н
6 HOOD 7 FIRE PROTECTION SYSTEM	10.0	120/1	В	VERIFY	INSTALL AND WIRE COMPLETE CONTROL PANEL. PROVIDE         ALL CONTROL WIRING AND MAKE ALL CONNECTIONS.         TIE FIRE SUPPRESSION SYSTEM INTO BUILDING FIRE         AL ARM SYSTEM AS REQUIRED	
Image: Profession system       Image: Professi	3.8	120/1	A	VERIFY	ALARM SYSTEM AS REQUIRED.           RECEPTACLE PROVIDED WITH WORK TABLE.           DOWN FROM ABOVE THRU WORK TABLE UTILITY CHASE	
2 WORK TABLE 3 HEATED CABINET PASS-THROUGH	20.0	120/1	A	CEILING	DOWN FROM ABOVE THRU WORK TABLE UTILITY CHASE FOR CONNECTION TO PROVIDED WORK TABLE MOUNTED PEDESTAL RECEPTACLES.	
5 REFRIGERATOR PASS-THROUGH	3.8	120/1	A	CEILING		G
CASH REGISTER/POS	6.78	120/1	A	+42" +5"	PROVIDE ALL INTERCONNECTING WIRING AND CONDUIT BETWEEN THIS ITEM AND THE OFFICE CPU. VERIFY IN FIELD. PEDESTAL MOUNTED - RECEPTACLE	
4 HOT FOOD SERVING COUNTER	17.3	208/1	A	+5"	PEDESTAL MOUNTED - RECEPTACLE	ESSIONAL SEAL:
7     MILK COOLER       9     HOT FOOD SERVING COUNTER	2.7	208/1	A A	+5"	PEDESTAL MOUNTED - RECEPTACLE PEDESTAL MOUNTED - RECEPTACLE	PROFES
COLD FOOD SERVING COUNTER	6.78	120/1	A	+5"	PEDESTAL MOUNTED - RECEPTACLE TWIST LOCK CORD AND PLUG ASSEMBLY.	
OD     DUPLEX CONVENIENCE OUTLET       CO     DUPLEX CONVENIENCE OUTLET	10.0	120/1	A	CLG AS INDICATED	SUPPLIED AND INSTALLED BY E.C.	F F
HEN EQUIPMENT SCHEDULE NOT	ES:					CONSULTANT:
A: FURNISH AND INSTALL CORD AND M MALE AND FEMALE, INCLUDING STR CONNECTORS. B: FURNISH AND INSTALL DIRECT CON	AIN FITTINGS AND CORD					
AND JUNCTION BOX AS REQUIRED. S: CONTRACTOR SHALL FURNISH AND IN POWER WIRING FOR THE HOOD FIRE AND THE HOOD. FURNISH AND INSTA	STALL ALL CONTROL AND SUPPRESSION SYSTEM					4464 Γ Ρ
STARTERS, RELAYS, SWITCHES, DISC BREAKERS, PULL STATIONS, ETC. AS I COMPLETE OPERATIONAL SYSTEM. VERIFY ALL MOUNTING HEIGHTS AND	ONNECTS, SHUNT TRIP REQUIRED FOR A					E AB
PRIOR TO ROUGH-IN.						s z ź
						ON CITY S ON CITY S /E SE, MA
	Hex Notes					
	MASSIL N EA					
<ul> <li>VERIFY LOCATION OF EQUIPMENT ON ROOF.</li> <li>KITCHEN EQUIPMENT NATURAL GAS SUPPLY SOLENOID VALVE. CONTRACTOR SHALL WIRE THE VALVE TO TURN OFF GAS</li> </ul>						E BROW
	AUL AUL					
						ÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅÅ
						PERMIT SET
						0% BID / PER
						07/12/23 10C
						B
						PROJECT NO2203-2DRAWN BYWAMCHECKED BYTJC
						DATE 07/12/23
						ENLARGED KITCHEN AREA
						A POWER PLAN
						SCALE: 1/4" = 1'-0" SHEET NO
						E-203