

## SECTION 122100 - HORIZONTAL LOUVER BLINDS

## PART 1 - GENERAL

## 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

## 1.2 SUMMARY

- A. This Section includes venetian blinds.
- B. Related Sections: The following Sections contain requirements that relate to this Section:
  - 1. Division 6 Section "Miscellaneous Carpentry" for wood blocking and grounds for mounting horizontal louver blinds.

## 1.3 SUBMITTALS

- A. General: Submit each item in this Article according to the Conditions of the Contract and Division 1 Specification Sections.
- B. Product data for each type of horizontal louver blind specified. Include printed data on physical characteristics.
- C. Shop drawings showing location and extent of blinds. Show installation details at and relationship to adjoining work. Include elevations indicating blind units. Indicate location of blind controls.
- D. Samples for initial selection in the form of manufacturer's color charts showing the full range of colors, textures, and patterns available for each type of horizontal louver blind indicated.
- E. Schedule of horizontal louver blinds using same room designations indicated on Drawings.
- F. Maintenance data for horizontal louver blinds to include in the operation and maintenance manual specified in Division 1. Include the following:
  - 1. Methods for maintaining horizontal louver blinds and finishes.
  - 2. Precautions for cleaning materials and methods that could be detrimental to finishes and performance.

## 1.4 QUALITY ASSURANCE

- A. Fire-Test-Response Characteristics: Provide horizontal louver blinds identical to those tested for the following fire-test-response characteristics as determined by UL or another testing and inspecting agency acceptable to authorities having jurisdiction.
  - 1. Test Method: NFPA 701.
  - 2. Rating: Pass.
- B. Single-Source Responsibility: Obtain each type of horizontal louver blind from one source and by a single manufacturer.

## 1.5 PROJECT CONDITIONS

- A. Field Measurements: Check actual horizontal louver blind dimensions by accurate field measurements before fabrication, and show recorded measurements on final shop drawings. Coordinate fabrication schedule with construction progress to avoid delaying the Work.
- B. Space Enclosure and Environmental Limitations: Do not install horizontal louver blinds until space is enclosed and weatherproof, wet-work in space is completed and nominally dry, work above ceilings is complete, and ambient temperature and humidity conditions are and will be continuously maintained at values near those indicated for final occupancy.

## 1.6 EXTRA MATERIALS

- A. Furnish extra materials described below that match products installed, are packaged with protective covering for storage, and are identified with labels clearly describing contents.
  - 1. Horizontal Louver Blinds: Before installation begins, furnish quantity of full-size units equal to 5 percent of amount of each size installed.

# PART 2 - PRODUCTS

## 2.1 MANUFACTURERS

- A. Available Products: Subject to compliance with requirements, horizontal louver blinds that may be incorporated in the Work include, but are not limited to:
  - 1. Bali-Classics; Springs Window Fashions Division, Inc.
  - 2. Riviera Dustguard; Levolor
  - 3. Model CL62; Hunter Douglas, Inc.

## 2.2 HORIZONTAL LOUVER BLINDS

- A. Louvers: Manufacturer's standard as follows:
  - 1. Aluminum.
  - 2. Nominal Louver Width: 1 inch.

- B. Tilt Operation: Manual with wand.
- C. Cord-Lock Operation: Cord lock; locks pull cord to stop blind at any position in ascending or descending travel.
- D. Cord Equalizers: Self-aligning to maintain horizontal louver blind position.
- E. Mounting: Jambs of windows. Walls shall be drilled for inserts (expansion shields).
- F. Colors and Patterns: Where manufacturer's standard products are indicated, provide horizontal louvers complying with the following requirements:
  - 1. Provide Architect's selections from manufacturer's full range of colors and patterns for horizontal louver blinds of type indicated.

## 2.3 FABRICATION

- A. Product Standard and Description: Comply with AWCMA Document 1029 for each horizontal louver blind unit consisting of louvers, rails, cord locks, tilting mechanisms, tapes, and installation hardware.
- B. Lifting and Tilting Mechanisms: Noncorrosive, self-lubricating materials.
- C. Unit Sizes: Obtain units fabricated in sizes to fill window and other openings as follows, measured at 74 deg F (23 deg C):
  - 1. Blind Units Installed Between (Inside) Jambs: Width equal to 1/4 inch (6 mm) per side or 1/2 inch (12 mm) total, plus or minus 1/8 inch (3 mm), less than jamb to jamb dimension of opening in which each blind is installed. Length equal to 1/4 inch (6 mm), plus or minus 1/8 inch (3 mm), less than head to sill dimension of opening in which each blind is installed.
  - 2. Blind Units Installed Outside Jambs: Width and length as indicated, with terminations between blinds of end-to-end installations at centerlines of mullion or other defined vertical separations between openings.
- D. Installation Fasteners: Not less than 2 fasteners per bracket, fabricated from metal noncorrosive to blind hardware and adjoining construction; support blind units under conditions of normal use.
  - 1. Provide Hilti; Toggler Anchor Bolt System or approved equal.
- E. Hold-Down Brackets: Manufacturer's standard, as indicated.
- F. Side Channels: Manufacturer's standard, as indicated.

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine substrates, areas, and conditions for compliance with requirements for installation tolerances and other conditions affecting performance of horizontal louver blinds. Do not proceed with installation until unsatisfactory conditions have been corrected.

### 3.2 INSTALLATION

- A. Install blinds level, plumb, and located so exterior louver edges in any position are not closer than 1 inch (25 mm) to interior face of glass lites.

### 3.3 ADJUSTING

- A. Adjust components and accessories for proper operation.

### 3.4 CLEANING

- A. Clean blind surfaces, according to manufacturer's instructions, after installation.
- B. Remove surplus materials, packaging, rubbish, and debris resulting from installation. Leave installation areas neat, clean, and ready for use.

### 3.5 PROTECTION

- A. Provide final protection and maintain conditions in a manner acceptable to manufacturer and Installer that ensure that horizontal louver blinds are without damage or deterioration at the time of Substantial Completion.

END OF SECTION 122100