

748

10' ALLEY

IRON PIN SET

N 69° 32' 10" E
78.00'

1 PIN FD.

R.R. SPIKE SET

RES.

PT. LOT 9323

0.121 ACRES

GAR.

N 69° 15' 30" E
77.85'

4 IN CONC. WALK
145' NO. 20.82'
LIES ON CONC. BLK

CONC. BLK. BLDG

PT. LOT 9323

0.136 ACRES

76.42'

R.R. SPIKE SET
@ E. EDGE CONC.

77.67'

S 69° 15' 30" W

CONC. WALK

76.42'

S 20° 56' 40" E

IRON PIN SET

EX. CURB LINE

LOT CORNER
4.56' WEST E
3.78' NO. OF
BACK CONC.
WALK

N 21° 05' 00" W

6TH ST. S.W. 60'

TREMONT AVE. S.W. 60'

SURVEY OF LOT NO. 9323

MASSILLON, STARK CO, OHIO

FOR PAUL WILLIAMS

BY ROBT F. WAGONER, REG. SURVEYOR

DRAWN BY

SCALE 1" = 20'

MATERIAL

CHK'D

DATE

DRAWING NO.

TRACED

APP'D

REVISIONS

NO.

DATE

BY


1

2

3

4

5



D E S C R I P T I O N

(South Part Of Lot No. 9323)

Commencing at a Railroad Spike at the northeast corner of Lot No. 9323, thence $S20^{\circ}56'40''E$ along the east line of said Lot No. 9323, a distance of 67.58' to an iron pin at the true place of beginning of the tract herein described;

Thence continuing $S20^{\circ}56'40''E$ along the east line of said Lot No. 9323, a distance of 76.42' to a point; said point being the southeast corner of Lot No. 9323;

Thence $S69^{\circ}15'30''W$ along the south line of Lot No. 9323, a distance of 77.67' to a Railroad Spike at the southwest corner of Lot No. 9323;

Thence $N21^{\circ}05'00''W$ along the west line of Lot No. 9323, a distance of 76.42' to a cross cut in a concrete walk;

Thence $N69^{\circ}15'30''E$, a distance of 77.85' to the true place of beginning, containing 0.136 acres.

Paul J. Wagner
SHERIFF
COUNTY OF CLATSOP
OREGON

D E S C R I P T I O N

(North Part Lot 9323)

Known as and being part of Lot No. 9323 in the City of Massillon, Stark County, Ohio and being more fully described as follows:

The true place of beginning of the tract herein described being at a Railroad Spike at the northeast corner of Lot No. 9323;

Thence $S20^{\circ}56'40''E$ along the east line of said Lot No. 9323, a distance of 67.58' to an iron pin;

Thence $S69^{\circ}15'30''W$, a distance of 77.85' to a cross cut in a concrete walk;

Thence $N21^{\circ}05'00''W$ along the west line of said Lot No. 9323, a distance of 67.96' to an iron pin at the northwest corner of said lot;

*Thence $N69^{\circ}32'10''E$ along the north line of said Lot No. 9323, a distance of 78.00' to the true place of beginning, containing 0.121 acres.

Robert J. Wagner
SURVEYOR

MAIN ST

WEST - MASSILLON

30' STONE FOUND

GRANT ST.

RIVERSIDE - ADD.

HOUSTON ST.

PORTNERS

West line lot #17 of Wetmore Fox & Binney's Amicable Subd.
R.R. 5, R. 8.

M. Jardy (V. 98 P. 459)

East line Partners Subd.
also east line Lot #16
W.F. & B. - See plat and
note R.R. 3, P. 206

10' Alley

10' Alley

W. TREMONT ST. 60'

I hereby certify that the above
is a correct plat of part of the
S. E. Q. R. of Sec. 7, Tp. 10, R. 9, in the
City of Massillon Ohio as surved
by me, July 12th. 1911.

T. W. Longabaugh
Deputy Surveyor.

F. B. Gilester
Co. Surveyor

